

HDMI CABLES & SPLITTERS

HDMI Cables

Hi-Speed HDMI Cable

High Speed, Male/Male Gold Plated with Black Rubber Jacket with Ferrite Core

- 91-800-1M 1 Meter
- 91-800-2M 2 Meters
- 91-800-3M 3 Meters
- 91-800-5M 5 Meters
- 91-800-8M 8 Meters
- 91-800-10M 10 Meters
- 91-800-15M 15 Meters



Hi-Speed HDMI Cable

High Speed with Ethernet, Male/Male Gold Plated with Black Rubber Jacket with Ferrite Core

- 91-804-1M 1 Meter
- 91-804-2M 2 Meters
- 91-804-3M 3 Meters
- 91-804-5M 5 Meters
- 91-804-8M 8 Meters
- 91-804-10M 10 Meters
- 91-804-15M 15 Meters
- 91-804-20M 20 Meters
- 91-804-25M 25 Meters



Hi-Speed Mini HDMI Cable

High Speed with Ethernet, HDMI Male to Mini HDMI, Gold Plated, High Density Multi-Shielded, ArmourFlex Braiding Protects Cable from Damage

- 91-801-1M 1 Meter
- 91-801-2M 2 Meters
- 91-801-3M 3 Meters
- 91-801-5M 5 Meters



Hi-Speed HDMI Cable

High Speed with Ethernet, Male/Male Gold Plated, Fully Shielded to Reduce EMI and Other Interference Sources, Flat ArmourFlex Protective Braiding Protects Cable

- 91-804PS-1M 1 Meter
- 91-804PS-2M 2 Meters
- 91-804PS-3M 3 Meters
- 91-804PS-5M 5 Meters



Hi-Speed 90° Adjustable HDMI Cable

High Speed with Ethernet, Male/Male Gold Plated, Adjustable Head for Easy Installation

- 91-804A-1M 1 Meter
- 91-804A-2M 2 Meters
- 91-804A-3M 3 Meters
- 91-804A-5M 5 Meters
- 91-804A-8M 8 Meters



Hi-Speed Micro HDMI Cable

High Speed with Ethernet, HDMI 19-pin Male to Micro HDMI 19-pin Male, Supports HD Resolutions Beyond 1080p and Deep Color

- 91-803-1M 1 Meter
- 91-803-2M 2 Meters
- 91-803-3M 3 Meters



HDMI Splitters

HDMI Splitter

One HDMI Input, Two HDMI Outputs

- Frequency Bandwidth:** 2.25Gbps
- Video Format:** VGA: 640x480, 800x600, 1024x768, 1280x1024
- DTV/HDTV:** 480i, 576i, 480p, 576p, 720p, 1080i, 1080p
- Max. Input Length from Source:** 20M
- Max. Output Transmission Length:** 20M
- Power Consumption:** 10/20W max
- Power:** 5V/DC
- Size:** 175 x 105 x 30mm
- Weight:** 0.6KG
- Color:** Silver or Black
- 91-360R**



HDMI Splitter

Two HDMI Inputs, Four HDMI Outputs

- Frequency Bandwidth:** 2.25Gbps
- Video Format:** VGA: 640x480, 800x600, 1024x768, 1280x1024
- DTV/HDTV:** 480i, 576i, 480p, 576p, 720p, 1080i, 1080p
- Max. Input Length from Source:** 5M
- Max. Output Transmission Length:** 20M
- Power Consumption:** 10/20W max
- Power:** 5V/DC
- Size:** 170 x 102 x 30mm
- Weight:** 0.8KG
- Color:** Silver or Black
- 91-360R-8**



HDMI Splitter

One HDMI Inputs, Four HDMI Outputs

- Frequency Bandwidth:** 3.4Gbps
- Video Format:** VGA: 640x480, 800x600, 1024x768, 1280x1024
- DTV/HDTV:** 480i, 576i, 480p, 576p, 720p, 1080i, 1080p
- Max. Input Length from Source:** 15M
- Max. Output Transmission Length:** 15M
- Power Consumption:** 10/20W max
- Power:** 5V/DC
- Size:** 175 x 105 x 40mm
- Weight:** 1KG
- Color:** Silver or Black
- 91-360R-4**

HDMI Splitter

Four HDMI Inputs, Eight HDMI Outputs

- Frequency Bandwidth:** 2.25Gbps
- Video format:** VGA: 640x480, 800x600, 1024x768, 1280x1024
- DTV/HDTV:** 480i, 576i, 480p, 576p, 720p, 1080i, 1080p
- Max. Input Length from Source:** 20M
- Max. Output Transmission Length:** 20M
- Power Consumption:** 10/20W max
- Power:** 5V/DC
- Size:** 175 x 105 x 40mm
- Weight:** 1KG
- Color:** Silver or Black
- 91-360R-8**

HDMI & DVI ADAPTERS

HDMI Adapters

HDMI to DVI-D Cable

HDMI to DVI-Digital

- 91-805-1M
- 91-805-2M
- 91-805-3M
- 91-805-4M
- 91-805-5M



DVI-D Dual Link to HDMI

DVI-Digital Male to HDMI Female

91-806



HDMI Keystone Insert

44-771-HDMI-WH



Single HDMI Wall Plate

91-910-1WH



Dual HDMI Wall Plate

91-910-2WH

HDMI to DVI-D Dual Link

DVI-Digital Female to HDMI Male

91-807



DVI Cables

DVI-D to DVI-D Cable

DVI Digital Dual Link

- 91-810-1M
- 91-810-2M
- 91-810-3M
- 91-810-5M



DVI-I to DVI-I Cable

DVI Digital Single Link

- 91-815-1M
- 91-815-2M
- 91-815-3M
- 91-815-5M



DVI-D to DVI-A Cable

Digital to Analog

- 91-820-1M
- 91-820-2M
- 91-820-3M
- 91-820-5M



DVI-A to DVI-A Cable

Analog to Analog

- 91-825-1M
- 91-825-2M
- 91-825-3M
- 91-825-5M



(Digital signal only - dual link)



DVI-D

(Digital signal only - single link)



DVI-I

(Analogue signal only)



DVI-A

DVI Adapters

DVI to VGA Adapter

DVI Digital/Analog-Dual Link Male to VGA Female

91-883

DVI to DFP Adapter

DVI Digital-Dual Link to DFP

91-890

DVI to VGA Adapter

DVI Digital/Analog-Dual Link Female to VGA Male

91-906

DVI Gender Changer

DVI Female to DVI Female

90-111-DVI-D



90-111-DVI-D



91-883



91-906



91-890

HDMI SWITCHES & REPEATERS

HDMI Switches

HDMI Switch

Credit Card Size

Switch Easily Between Any Two HDMI Sources

Video Amplifier Bandwidth: 140MHz

Input Video Signal: 0.5-1.0 Volts p-p

Input DCC Signal: 5 Volts p-p (TTL)

Maximum Single Link Range: 1280 x 1024, 1080p

Video Format Supported:

VGA: 640x480, 800x600, 1024x768, 1280x1024

DTV/HDTV: 480i, 576i, 1080i, 480p, 576p, 720p, 1080p

Output Video: HDMI 1.3+HDCP1.0/1.1

Vertical Frequency Range: 60Hz

Power Consumption: 10 Watts

Power Supply: 5V/DC

Dimensions (LxWxH): 85mm x 15mm x 43mm

Weight: 80g



91-362

HDMI Switch

Compliant to HDMI 1.3b, HDCP 1.2

Ideal for Home Theater Integration

Support High Resolution Input:

PC: VGA, SVGA, XGA, SXGA, and UXGA

HDTV: 480i, 576i, 480p, 576p, 720p, 1080i, 1080p

Without Power

Easy to Install and Simple to Operate

3 Female HDMI Inputs

1 Female HDMI Output

Dimension (LxWxH): 175mm x 105mm x 30mm

Weight: 0.65kg



91-363

HDMI Switch

Compliant to HDMI 1.3b, HDCP 1.2

Ideal for Home Theater Integration

Support High Resolution Input:

PC: VGA, SVGA, XGA, SXGA, and UXGA

HDTV: 480i, 576i, 480p, 576p, 720p, 1080i, 1080p

Without Power

Easy to Install and Simple to Operate

4 Female HDMI Inputs

1 Female HDMI Output

Dimension (LxWxH): 175mm x 105mm x 30mm

Weight: 0.65kg



91-364

HDMI Repeaters

HDMI Repeater

Perfect Digital Video Sent Over Long Stretches of HDMI Cables

Input/Output Connector: HDMI Type A (19 Pin)

Amplifier Bandwidth: 1.65GHz

Max Input Cable Length: 50m

Max Output Cable Length: 5m

DTV/HDTV: 480i, 576i, 480p, 576p, 720p, 1080i, 1080p

Power Adapter: 5V/DC

Enclosure: Metal

Dimensions: 66 x 67 x 24mm

Weight: 66g



91-360

HDMI Extender

This Kind of HDMI Extender Uses Two Pieces of CAT-5e/6 Cables to Extend the HDTV Display up to 60 Meters for 1080p

Input Video Signal: 0.5-1.0 Volts p-p

Input DDC Signal: 5 Volts p-p (TTL)

Maximum Single Link Range: 1920x1200, 1080p

Output Video: HDMI 1.2a

DTV/HDTV: 480i, 576i, 480p, 576p, 720p, 1080i, 1080p

Transmission Distance: 60m for 1080p & 100m for 480p

Power Supply: 5V/DC

Dimensions: 45 x 25 x 81mm

Weight: 0.246kg



91-860

HDMI CONVERTERS

HDMI Converters

YPvPr to HDMI Converter

Allows You to Connect YPbPr HDTV Sources to an HDMI Display

Input DDC Signal: 5 Volts p-p (TTL)

HDMI Connector: Type A (19 Pin) Female

Video Connector: 3 RCA Component

Audio Connector: SPDIF

Output Video: HDMI 1.2a

HDTV Resolutions: 480i, 576i, 1080i, 480p, 576p, 720p, 1080p

Vertical Frequency Range: 50/60Hz

Frequency: 1.65Gpbs/165MHz

Power Consumption: 5 Watts

Power Supply: 5V/DC

Dimensions (LxWxH): 88mmx25.5mmx68mm

Weight: 0.12kgs



HM-3039

SVGA to HDMI Converter

Converts PC's VGA Video and R/L Audio into Complete HDMI

Input Video Signal: 0.5-1.0 volts p-p

Input DDC Signal: 5 Volts p-p (TTL)

Output Video: HDMI 1.2a

VGA Resolution: 640x480, 800x600, 1024x768, 1280x720, 1280x768, 1280x960, 1280x1024

Vertical Frequency Range: 50/60Hz

Video Amplifier Bandwidth: 1.65Gpbs/165MHz

Power Consumption: 5 Watts

Power Supply: 5V/DC

Dimensions (LxWxH): 88mmx25.5mmx68mm

Weight: 0.68kgs



HM-3040

DVI + Audio to HDMI Converter

Allows You to Connctet Computers or Other Sources with

DVI Output and SPDIF to an HDMI Display

Input DDC Signal: 5 Volts p-p (TTL)

Input Video: DVI 1.1v

Output Video: HDMI 1.3b

HDMI Connector: Type A (19 Pin) Female

DVI-I (29 Pin) Female (Digital Only)

Audio Connector: Toslink Audio and Digital Audio

HDTV Resolutions: 480i, 576i, 1080i, 480p, 576p, 720p, 1080p

Vertical Frequency Range: 50/60Hz

Video Amplifier Bandwidth: 2.25Gpbs/225MHz

Power Consumption: 5 Watts

Power Supply: 5V/DC

Dimensions (LxWxH): 87.5mmx67.5mmx25.5mm

Weight: 260g



HM-3041

S-Video to HDMI Converter

Converts S-Video up to HDTV 720p

Input Video Signal: 1.2 Volts p-p

Input DDC Signal: 5 Volts p-p (TTL)

Output Video: HDMI

DTV/HDTV: HDMI 720p@60Hz

HDMI Connector: Type A (19 Pin) Female

Vertical Frequency Range: 50/60Hz

Video Amplifier Bandwidth: 1.65Gpbs/165MHz

Power Consumption: 5 Watts

Power Supply: 5V/DC

Dimensions (LxWxH): 155mmx70mmx23mm

Weight: 255g



HM-3042