



Mixer Amplifier	
WA-612E	
Model	WA-612E
Power Output (RMS)	120W
Power Supply	AC 115/230V 50/60Hz, DC 24V
Total Harmonic Distortion	<=1%@1 KHz
Sensitivity	XLR (BALANCED) CHANNEL 1~3 (MIC 1~3) 1 mV @ 600W TEL (TERMINAL) 100 mV @ 600W CHANNEL 4 (MIC 4) 0.5 mV @ 600W AUX 1(RCA), 100mV @ 22KW CHANNEL 5 (MIC 5) 100mV @600W AUX 2(RCA), 100mV @22KW AUX 3(RCA), 100mV@22KW TYPE OUT (RCA), AUX OUT(RCA) 1V
Frequency Response	50 HZ ~ 20K Hz +/-3dB
Output	100 V, 70 V, 8W
Signal to Noise Ratio	86dB
Chime Input	MIC 5
Voice Priority Mute	MIC 1
Phantom Power Adjustable	MIC 1~5
Tone	BASS 100Hz ± 10dB TREBLE 10KHz ± 10dB
AC Power Consumption (@ RATED POWER)	320W
DC Power Consumption (@ RATED POWER)	8A
Dimension	88(H) x 425(W) x 305mm (D)
Weight	9.5 kgs
Mounting	FREE STANDING OR 19' RACK

Winston International

200 Hillsboro Street P.O.Box 1608 Oxford, Nc 27565 Phone: 919-693-1561 Toll Free: 1-800-1411 Fax: 919-693-5257
www.winstonele.com