



\* NOTE: All relevant materials are complied with RoHS directive .

P1	9F17	P2
1		1 RED CONDUCTOR
2		2 RED SHIELD
3		3 GREEN CONDUCTOR
4		4 GREEN SHIELD
5		5 BLUE CONDUCTOR
6		6 BLUE SHIELD
7		7 SHIELD
8		8 SHIELD
9		9 SHIELD
10		10 SHIELD
11		11 SHIELD
12		12 SHIELD
13		13 SHIELD
14		14 SHIELD
15		15 SHIELD

No.	DESCRIPTION	QTY	Supplier
1	FLASH ON CONTACTS, METALLIZE TYPE, BLUE INSULATOR	1	M108
2	HD15 FEMALE WITH THREADED NUT(2PCS) INSIDE, 4.75*5.5mm, GOLD FLASH ON CONTACTS, METALLIZE TYPE, BLUE INSULATOR	1	M108
3	SCREW #4-40, LENGTH 6.25*25.5mm	4	M95
4	MOLDED PVC BLACK		M304
5	FERRITE CORE 14.3*6.35*28.5mm	2	M113
6	UL20278 E32WGT(C+D+FM)+3C+9C*30MMGT+AL+D+B, 00 4.6mm, JACKET BLACK 4880mm	2	M298
	MOLDED PE COLOR TRANSPARENT		M304
	COOPER FOL 17*65mm	2	TWN
	MOLDED PVC BLACK		M304
	BLACK HEAT SHRINK TUBE Ø3.0*5mm	6	M743
	BLACK HEAT SHRINK TUBE Ø1.0*5mm	6	M743
	BLACK HEAT SHRINK TUBE Ø3.0*10mm	2	M743
	COPPER FOL 17*65mm	2	M309

APPROVED	
CHECKED	TIAN
DRAWING	XIANG
DATE	20/JUN/08
ITEM NO.	90-920-15SVGA

# Welttron

UNIT/mm	Supplier
Cable Length	±10mm
Wireless	±20mm
Other Spec.	±25mm
0 ~200mm	±30mm
201 ~500mm	±35mm
1001 ~1500mm	±40mm
1501 ~2100mm	±45mm
2100mm+	±40mm

CHECKED