



• NTOE: All relevant materials are complied with RoHS directive .

4	MOLDED PVC BLACK BLACK HEAT SHRINK TUBE #2.5*8mm COPPER FOIL 24*60mm COPPER FOIL 7.5*40mm	10 2 2	M304 M743 M309 M309
3	MOLDED PE COLOR TRANSPARENT DISPLAYPORT 20PIN PLASTIC HOOD BLACK	2set	M280 M24
2	UL20276 (2BAWG*1PR+D+AL/ANTLAR)*5+2BAWG*4C+AL/ANTLAR+BRAID, OD 7.3mm, JACKET BLACK, IMPEDANCE: 100 Ohm	L-20mm	M299
1	DISPLAYPORT 20PIN PLUG, GOLD PLATING 30μ' ON CONTACTS & GOLD CONNECTOR, BLACK INSULATOR, PCB ASSEMBLY TYPE	2	M24

Weltron

RE.2 2008.11.24	MODIFY CABLE INSULATION COLOR & MODIFY MODEL	CHECKED
RE.1 2008.11.04	MODIFY PLUG	CHECKED

APPROVED			
CHECKED	HU		
DRAWING	XIANG		
DATE	24/NOV/08	ITEM NO.	91-900-2M

UNIT:mm		
Cable Length	0-200mm	±10mm
Insulation Thickness	201-1000mm	±25mm
	1001-1500mm	±25mm
	1501-2100mm	±30mm
	2100mm+	±40mm